

Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

Y4988 - Asphalt Anchor Kit For Mounting Sign Base

Asphalt Anchors Kit Include all of the following:

- 4 Asphalt anchors
- 4 One inch long -full thread- bolts
- 4 Washers
- 2 Bags of anchor grout (14oz)

ANCHOR SPECS

Details	6" Anchor
Pull Rated	1,500 lb
Shear Rated	1,000 lb
Torque Rated	220 lb-in.
Thread	3/8"
Thread Depth	2.5"
Length	6"
Drill Hole	7/8"

X2 Ar Expansions Contracts Adds 2 see Mardens i Curves Ses Assphalit Assphalit Rations is 5 minutes Cortises 14 ag weight Add 2 or winter, kneed Haddens is 5 minutes Curve in 1 hour Dot 20 deg AssphalitAncheron-cons

Installation Steps

- 1. Drill holes (4) per anchor specs above
- 2. Fill holes with grout (1 bag of grout per every 2 holes)
- 3. Push anchors in flush with surface and wait 15 minutes...
- 4. Attach fixed base to anchors by using the 1" long bolts and washers supplied









DATE://	JOB:	

CONTRACTOR: