

Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

P1051 - Reusable Corded Ear Plugs



ANSI
S3.19

NRR
25
dB

DURAPLUGS™ EAR PLUGS

TECHNICAL INFORMATION

International Standards	ANSI S3.19
Color	Red flange, yellow base
Sizes Available	One Size
Materials	Polyurethane foam, poly cord
Hearing Style	Corded, Foam, Reusable
dB	25
Applications	Food Processing, Manufacturing
Country of Origin	Taiwan
Harmonization Code	3926.90.9985

- Unique reusable 3-layer flange fits all size ear canals
- Firm stem for easy insertion and removal
- Washable and reusable
- Noise reduction rating (NRR): 25dB
- Each pair individually wrapped
- Corded

INFORMATION REQUIRED BY EPA:

The level of noise entering a person's ear, when a hearing protector is worn as directed, is closely approximated by the difference between the A-weighted environmental noise level and the NRR.

Example:

1. The environmental noise level as measured at the ear is 92 dBA.
2. The NRR is 33 decibels (dB).
3. The level of noise entering the ear is approximately equal to [92 dB (A) - 33] 59 dB (A).

CAUTION: For noise environments dominated by frequencies below 500 Hz the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Consult the enclosed instructions for proper fit. Although hearing protectors can be recommended for protection against the harmful effects of impulsive noise, the Noise Reduction Rating (NRR) is based on the attenuation of continuous noise and may not be an accurate indicator of the protection attainable against impulsive noise such as gunfire.

 **WARNING:** Risk of Cancer & Reproductive Harm from Di(2-ethylhexyl)phthalate Exposure - For more information, go to www.P65Warnings.ca.gov.

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____