

Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

Safety Sign G5720



Compliance: OSHA / ANSI Z535.2

SIGN SIZE W x H	HEADER SIZE	GRAPHIC SIZE	Biohazard Text Size	Authorize Text Size
10 x 7"	1-3/16"	3.5"	5/8"	1/2"
14 x 10"	1-3/4"	5"	1"	5/8"

STANDARD MATERIALS AVAILABLE		STOCK SIGN SIZES* Width x Height	
Select	Description	10 x 7" 254 x 179 mm	14 x 10" 356 x 254 mm
<input type="checkbox"/>	Label: Adhesive Backed Vinyl	X	X
<input type="checkbox"/>	.055 Plastic	X	X
<input type="checkbox"/>	.040 Aluminum	X	X

* Many more sizes available upon request

Mounting Options:

- Labels are supplied with back adhesive, no holes required.
- Plastic and Aluminum signs are supplied with 4 mounting holes:
10 x 7" and 14 x 10" have 0.218 dia. holes
- Safety Signs have been designed for the following applications: fence, wall or any flat surface mounting

Safety Sign Fonts:

- Standard fonts use: Arial Black

DATE: ___ / ___ / ___ JOB: _____

CONTRACTOR: _____



Product Information Bulletin

64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809

Safety Sign Colors & Materials

Standard Ink Colors*: (Close PMS Color Match)

Black (PMS Black)

Safety Orange (144C)

Material Information

MATERIAL THICKNESS	MATERIAL NAME	CHEMICAL RESISTANCE	OUTDOOR DURABILITY	TEMP RANGE	CORNER RADIUS	MOUNT HOLES
3.5 Mil	Adhesive Backed Vinyl	Fading & Mild Chemicals	4 to 5 years	-20°F to 200°F -29°C to 93°C	1/4" (6.3mm)	None
<ul style="list-style-type: none"> • Outdoor Grade 3.2 mil thick high gloss adhesive backed calendered vinyl film, printed using UV and chemical resistant inks, to ensure durability in most commercial / industrial environments. • Coated with Aggressive Acrylic Adhesive formulated to adhere to a variety of insulated and non insulated pipe surfaces • Min. Application Temp: 50° F (10°C) • Surface Preparation: Clean and Dry • LEED Compliance: <p>This product is in compliance with the Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule #1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC).</p>						

.055" 1.4mm	Polyethylene Plastic	Fading & Mild Chemicals	3 to 5 Years	-40°F to 180°F -40°C to 82°C	1/4" 6.3mm	4 @ 7/32" 5.5mm
<ul style="list-style-type: none"> • Polyethylene is a rust free, chip and crack resistant plastic • Polyethylene signs are an economical alternative to aluminum signs, without significant compromise on durability. • Material Flexibility: .055" thick bends easily without causing material fractures, could be molded to fit certain surfaces. • Mounting: Wall or fence mounting only. 						

.040" 1mm	Aluminum Coated with Baked Enamel	Fading and Mild Chemicals	5 to 7 Years	-40° to 212° F -40° to 100° C	1/4" 6.3mm	4 @ 7/32" 5.5mm
<ul style="list-style-type: none"> • Aluminum offers longer life expectancy and better resistance to harsh weather conditions. • Aluminum will not chip, crack or rust. • Overlaminated Options (Additional Charge): 3M Anti Graffiti Over Laminate • Mounting: Wall or fence mounting only. 						

DATE: ___ / ___ / ___ **JOB:** _____

CONTRACTOR: _____